



Confidential Report

Our Ref: 27/06138B/04/23



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.
Telephone: +44 (0) 113 259 1999
Email: onestopshop@bttg.co.uk
Website: www.bttg.co.uk

Date: 22 May 2023

Our Ref: 27/06138B/04/23

Your Ref: ---

Page: 1 of 8

Client: Kalsi Group (UK) Ltd

Kalsi House
5 Tomey Road
Tyseley
Birmingham
B11 2NJ

Job Title: Fire Test on One Sample of Interlocking Cladding Boards

Clients Order Ref: --

Date of Receipt: 17 April 2023

Description of Sample: One sample of interlocking cladding boards, referenced; Embossed Cladding Platinum Grey.

Work Requested: We were asked to make the following test(s):

BS EN 13823

* subcontracted test, UKAS accredited
** subcontracted test, EN ISO/IEC 17025 accredited
*** not UKAS accredited

Note: This report relates only to the items tested.

Shirley® Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL.
A company registered in England & Wales with company number 04669651. VAT Number GB 816764800.
BTTG™ and Shirley® are trade names of Shirley Technologies Ltd.
The supply of all goods and services is subject to our standard terms of business, copies of which are available on request.
Our laboratories are accredited to EN ISO/IEC 17025.

Copyright © 2023 Shirley Technologies Limited. All rights reserved.



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.
Telephone: +44 (0) 113 259 1999
Email: onestopshop@bttg.co.uk
Website: www.bttg.co.uk

Date: 22 May 2023

Our Ref: 27/06138B/04/23
Your Ref: ---

Page: 2 of 8

Client: Kalsi Group (UK) Ltd

FIRE TESTS ACCORDING TO BS EN 13823:2020 (INDICATIVE) ***

Reaction to fire tests for Building Products - Building Products excluding floorings exposed to the thermal attack by a single burning item.

Classified According to BS EN 13501-1:2018

Date of Test: 22/05/2023

Conditioning

One specimen from the sample was conditioned otherwise in accordance with BS EN 13238:2010.

Principle

A test specimen, consisting of two vertical wings forming a right-angled corner, is exposed to the flames of a burner placed at the bottom of that corner. The flames are obtained by the combustion of propane gas, injected through a sandbox to give a heat output of $30.7 \pm 2.0 \text{ kW}$.

The performance of the test specimen is evaluated over a period of 20 minutes. The performance requirements are: heat production, smoke production, lateral flame spread and falling flaming droplets and particles.

The heat production is measured by use of oxygen calorimeter that uses the principle that the amount of oxygen consumed in a fire is proportional to the amount of heat produced. The smoke production is measured by use of a light attenuation instrument installed in the exhaust duct alongside the sampling equipment used to measure the heat release. Visual observations are made of the horizontal flame spread and falling of flaming droplets and particles.



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.
Telephone: +44 (0) 113 259 1999
Email: onestopshop@bttg.co.uk
Website: www.bttg.co.uk

Date: 22 May 2023

Our Ref: 27/06138B/04/23

Your Ref: ---

Page: 3 of 8

Client:

Kalsi Group (UK) Ltd

Photograph Of Sample





Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.
Telephone: +44 (0) 113 259 1999
Email: onestopshop@bttg.co.uk
Website: www.bttg.co.uk

Date: 22 May 2023

Our Ref: 27/06138B/04/23
Your Ref: ---

Page: 4 of 8

Client: Kalsi Group (UK) Ltd

Procedure

The test was carried out otherwise in accordance with BS EN 13823:2020.

The specimen was assembled with the cladding boards interlocking with one another forming horizontal joints and then screwed onto a 12mm calcium silicate board, and tested as defined in BS EN 13238:2010.

The specimen was placed in the trolley as per the instructions given and placed underneath the hood in the testing chamber. The volume flow of the exhaust was set to $0.60 \pm 0.05 \text{ m}^3/\text{s}$ and maintained at this throughout the test period.

The temperatures in the exhaust hood and the ambient temperature should be within 4°C with the ambient temperature being within $20 \pm 10^\circ\text{C}$. The other pre-test conditions of ambient pressure and ambient relative humidity were also recorded.

The recording of baseline data is started at 0 s. At 120 s the auxiliary burner is ignited and the propane mass flow adjusted to the specified flow before 150 s, this flow to be kept constant throughout the test.

With the pre-test conditions met, the propane supply is switched from the auxiliary burner to the main burner at 300 s.

The burning behaviour of the specimen was recorded both automatically and visually over a period of 1,260 s from when the main burner was ignited.

At 1560 s the gas supply was terminated along with the automatic recording of the data. The conditions at the end of the test were recorded at least one minute after any remaining combustion has been totally extinguished.

The individual pre-test and baseline conditions, apparatus specifications, test validity criteria, burner details was found to be within specified parameters. The graphs of HRR, HRR(30), THR, FIGRA, SPR, SPR(60), TSP and SMOGRA are found below with the results and classification.



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.
Telephone: +44 (0) 113 259 1999
Email: onestopshop@bttg.co.uk
Website: www.bttg.co.uk

Date: 22 May 2023

Our Ref: 27/06138B/04/23
Your Ref: ---

Page: 5 of 8

Client: Kalsi Group (UK) Ltd

Classification Criteria

The sample was classified according to BS EN 13501:2018 Fire classification of Construction Products and Building Elements: Part 1: Classification using Test Data from Reaction to Fire Tests.

For construction products excluding floorings the classes are:

Classification	Classification Criteria (mean values)			
	FIGRA _{0.2MJ} (W/s)	FIGRA _{0.4MJ} (W/s)	LFS	THR _{600s} (MJ)
A2	≤120	N/A	Edge of specimen	≤7.5
B	≤120	N/A	Edge of specimen	≤7.5
C	N/A	≤250	Edge of specimen	≤15
D	N/A	≤750	No requirement	No requirement

To meet classification A2 the sample also has to meet the requirements of either BS EN ISO 1182 or BS EN ISO 1716.

To meet classification B, C and D the sample also has to meet the requirements of BS EN ISO 11925-2.

Additional Classifications - Smoke and Flaming droplets/particles

Classification	Classification Criteria (mean values)	
	SMOGRA (m ² /s ²)	TSP _{600s} (m ²)
s1	≤30	≤50
s2	≤180	≤200
s3	Not s1 or s2	Not s1 or s2
d0	No flaming droplets/particles within 600seconds	
d1	No flaming droplets/particles persisting longer than 10 seconds within 600 seconds	
d2	Not d0 or d1	



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.
Telephone: +44 (0) 113 259 1999
Email: onestopshop@bttg.co.uk
Website: www.bttg.co.uk

Date: 22 May 2023

Our Ref: 27/06138B/04/23
Your Ref: ---

Page: 6 of 8

Client: Kalsi Group (UK) Ltd

Results

Classification criteria		Class
FIGRA _{0.2MJ} (W/s)	229.2	C
FIGRA _{0.4MJ} (W/s)	203.2	
THR _{600s} (MJ)	11.1	
LFS to edge (yes or no)	No	
SMOGR _A (m ² /s ²)	188.0	s3
TSP _{600s} (m ²)	535.1	
FDP flaming ≤ 10 s (yes or no)	No	d0
FDP flaming > 10 s (yes or no)	No	

Note

The test results relate to the behaviour of the test specimen of a product under the particular conditions of the test; they are not intended to be the sole criteria for assessing the potential fire hazard of the product in use.

Only one specimen was tested to BS EN 13823:2010. No guarantee can be given as to the outcome of definitive testing. This report does not have the status of a full UKAS Accredited Test Certificate, therefore, it cannot be substituted or used as such.

Test BS EN 13823:2020 is accredited under our flexible scope policy.

Comments

The results meet the requirements of a Class C, s3, d0 when tested to this method alone.

To meet classification B, C and D the sample also has to meet the requirements of BS EN ISO 11925-2:2020.



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.
Telephone: +44 (0) 113 259 1999
Email: onestopshop@bttg.co.uk
Website: www.bttg.co.uk

Date: 22 May 2023

Our Ref: 27/06138B/04/23

Your Ref: ---

Page: 7 of 8

Client: Kalsi Group (UK) Ltd

Where required to make a judgement to any pass/fail criteria an estimation of uncertainty of measurement has been taken into account. Under our Policy we have used a non-binary decision rule.

See our decision rules Policy (<https://www.bttg.co.uk/about-us/decision-rules-policy/>) for further information.

Reported by:.....*B Marsden*..... B Marsden (Mrs), Senior Fire Technician

Countersigned by:.....*A Shute*..... A Shute, Section Leader

Enquiries concerning this report should be addressed to Customer Services.



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.
Telephone: +44 (0) 113 259 1999
Email: onestopshop@bttg.co.uk
Website: www.bttg.co.uk

Date: 22 May 2023

Our Ref: 27/06138B/04/23

Your Ref: ---

Page: 8 of 8

Client: Kalsi Group (UK) Ltd

Uncertainty Budget

The uncertainty budget for BS EN 13823:2020 was determined as follows:-

FIGRA 0.2MJ	±15%
FIGRA 0.4MJ	±15%
THR 600s	±10%
SMOGRA	±15%
TSP 600s	±20%